

SUPERHERO Software Tool User Manual



LIFE SUPERHERO LIFE19 CCA/IT/001194



Content

1.	SUPERI	HERO software general concept	3
2.	Installa	tion and run of the software tool	4
3.	Use Gu	ide	8
3.	1 Menu		8
3.	2 Home		8
	3.2.1 R	oof Energy Performance	9
	3.2.2 Li	fe Cycle Costing	13
	3.2.3 Li	fe Cycle Assessment	15
3.	3 Expor	t	17
3.	4 Edit		17
	3.4.1 Ed	dit > Materials	17
	3.4.2	Edit > Roofs	19
	3.4.3	Edit > Walls	20
	3.4.4	Edit > Economic data	21
	3.4.5	Edit > Database of EPD and Impact Tables	22
	3.4.6	Edit > Create a new Impact Table	23
	3.4.7	Edit > Energy Use Conversion Factors	24





1. SUPERHERO software general concept

SUPERHERO software is able to easily assess the following results for a new roof, including an HBR, also in comparison with another reference roof:

- the dynamic heating and cooling energy performance, considering the roof installed on an attic space;
- the external roof covering maximum temperature;
- Global Costs, Cumulative Discounted Cash Flows and Payback Period, considering the initial, maintenance and energy costs difference among the two roofs;
- the environmental impacts of the new roof based on product and operational cooling energy use stages.

The figure provides the general software architecture.



In 4 specifically developed modules, the user inserts input data or modifies data already included in databases.

The user selects the attic location, geometry, orientation and features of walls, windows and roofs (for the design roof and the reference roof). He/she can use the materials' data stored in databases or create new materials and stratigraphies. These inputs dynamically modify a parametric model in Energy Plus Software, then the energy performance is assessed, and the roof external surface temperature also obtained.

The calculated energy consumption is needed to assess the costs and impacts during the building use phase. For LCC, the user specifies economic data inputs to obtain the Global Cost and Payback Period.

The environmental data can be inserted in a specific module, and the user can upload EPDs for specific materials in XML format.



The software code is written in python language and the visual interface provided by a Dash web app. Energy Plus simulations are run inside the code after updating a parametric file with input data defined by users (next figure).



2. Installation and run of the software tool

- a. Install docker desktop software: Install Docker Desktop on Windows | Docker Docs
- b. Once installed, launch the software and if this window appears at startup, type the suggested string in the command prompt



c. In the "Search" bar above, search for the user simas023 (or direct link from browser: <u>simas023/dash-eplus - Docker Image | Docker Hub</u>)

👉 docker desktop 🛛 Personal		Q Search for images, containers, volumes, extensions Ctrl+K 😌 🏺 🛞	🔢 Sign in 🗕 🗇 🗙
G Containers	Containers Give feedback G	· K /	
() Images			
C. Volumes	Container CPU usage 🥡	Container memory usage	Show charts
🖉 Builds	0.00% / 800% (8 CPUs available)	0B / 3.68GB	
💓 Docker Scout	O Crarek	00 - Osluskawannias santainas	
Extensions	Q search	UU Uniy snow running containers	





d. Press "Pull" to load the software image among your images within your Docker Desktop

simas023							Q
Images (1)	Containers (0)	Volumes (0)	Extensions (0)	Docs (0)			
S Hub images	(1) Remote re	epositories (0)	Local images (0)			,	
<u>simas023</u>	/dash-eplus			± 19 · ★ 0	Tag 0.0.17	Pull	Run
e to open	t i to navig	ate E	sc to close	SCROLL for	more results	Give	teck 🖳





e. click on "Images" on the left, the "simas023/dash-eplus" image will appear. Press "play" (on the right, under "Actions")

- docker desktop (Personal)			Q Search: simas023		Ctrl+K	ণ্ড	•	۵ III	Sign in	-	٥	×
1 Containers <	Images Give feedback 3											
(ŷ) Images	Lord the											
	Local Hub											
Builds	5.69 GB / 5.69 GB in use 2 images							Last	refresh: 37 min	utes ago	C	
Docker Scout											-	
Extensions	Q Search	Ξ 00										
	Name		Tag	Status		Created	ł	Size	2 Action	15		
	simas023/dash-eplus 02bfba86d47e		0.1.7	<u>In use</u>		12 days	ago	1.69	GB ▷	:	Ū	
										K		

f. In the "Optional settings" screen, type 0 on "Ports"

Run a new contain simas023/dash-eplus:0.0	er 0.12	
Optional settings		^
Container name		
A random name is generated if you do	o not provide one.	
Enter "0" to assign randomly generate Host port 0 Volumes	ed host ports.	:80/tcp
Host path …	Container path	+
Environment variables		
Variable	Value	+
	Cancel	Run





Hocker desktop (Personal)	Q Search: simas023 Ctrl+K 🛛 🧐 🗰 🍪 🗰 Sig	jn in 🛛 —
Containers	SuperHero Simas023/dash-eplus:0.1.7 c0d1a4f37a2f (1) 32769:80 (2) 3	C (
Builds	Logs spect Bind mounts Exec Files Stats	

g. Press the link in the new screen that appears:

h. To end use, press "stop".

			Q Search: simas023	Ctrl+K	8 🕯	@ III	Sign in 🛛 —
Containers	< 😭	SuperHero simas023/dash-eplus:0.1.7 c0d1a4f37a2f			STATUS Running	S g (1 second ago	
Builds	Logs	nspect Bind mounts Exec	Files Stats				





3. Use Guide

Once the App is launched, the internet browser opens, and the **home page** appears.

▼ ■ Home × +		- 0 ×						
$\leftrightarrow \rightarrow$ C (i) localhost:32770		☆ :						
88								
IN SUPERHERO		* (
Home Export - Edit - Help								
ROOF ENERGY PERFORMANCE	LIFE CYCLE COSTING	LIFE CYCLE ASSESSMENT						
	Input Data Energy simulation of an attic floor							
	Select Nearest Climatic Location							
	EUROPE	×						
	ITA - Italy	× +						
	Ancona	X v						
	Weather File Selected : Ancona							
	Attic Floor Type							
	Gable	X *						
	Orientation and Geometry							
	N	X *						

3.1 Menu

- A. The tool web interface contains the menu on the top left with the following items: *Home, Export, Editing, Edit, Help*.
- **B.** To switch between a light (day) and dark (night) theme, you will need to adjust the button on the top right.



3.2 Home

The **home page** contains the main menu with the following items:

- A. ROOF ENERGY PERFORMANCE: to perform an energy simulation of an attic floor
- **B.** LIFE CYCLE COSTING: to carry out a life cycle assessment of the economic performance based on cooling energy benefits of the new roof
- **C.** LIFE CYCLE ASSESSMENT: to perform an environmental impact assessment of the new roof based on product and operational cooling energy use stages







3.2.1 Roof Energy Performance

In the Roof Energy Performance page, the first section is the **Input Data** where it is possible to:

• Choose the **Climatic Location** by either scrolling through the drop-down menu or typing the city name directly

ROOF ENERGY PERFORMANCE	LIFE CYCLE COSTING							
	Input Data Energy simulation of an attic floor							
Select Nearest Climatic Location								
EUROPE * -								
ITA - Italy 🔹 -								
Select	Ancona 🔶 Type	×						
Ancona-Falconara								
Ancona								

• Choose the Attic Floor Type by scrolling through the drop-down menu

,	Attic Floor Type	
	Gable ×	
Flat		5
Shed		
Gable		
	h ¹ h ² y	

• Select the building's plan **Orientation** by scrolling through the drop-down menu or typing "N", "N-E", "E", "E-S", "S", "S-W", "W-N"

Orientatio	on and Geometry
	N-W × ^
E	۵
S-E	
S	
S-E	
W	
N-W	• •
	Wall C
Wall D	Wall A





• Specify the walls **Geometry** by entering the length [m] and height [m] of walls in the designated fields

		Wall C		1	
	Wall D		Wall B	у	
	L	Wall A			
Lenght x [m]	Lenght y [m]			Height h1 [m]	Height h2 [m]
10,55	6,00			3,20	3,50

• In the designated fields specify the **window surface**, for each wall, as a percentage [%] of the total wall surface

	Windows					
	Window surface compared to the wall surface [%]					
Windows Wall A [%]	Windows Wall B [%]	Windows Wall C [%]	Windows Wall D [%]			
15	0	15	15			

 Then the user can define the wall stratigraphy in the "Select Walls" section. A selection of predefined wall types is available in drop-down menu (A). Once a wall is selected, its stratigraphy will be displayed in table (B).

Alternatively, the user can create a custom stratigraphy on the *Edit > Walls* page (see guide Section *3.4.3 Edit > Walls*).

Note: The same stratigraphy is applied for all the walls and for both reference and new case studies.

			Select Walls ①				
	A Wall_03						
R	Material Name	Thickness [m]	Thermal Conductivity [W/mK]	Density [kg/m3]	Specific Heat [J/kgK]		
	Plaster - MapeWall	0.02	0.9	1250	1000		
	Hollow clay brick - Ziegel - 12 cm	0.12	0.258	620	1000		
	Air gap - 4 cm	0.04	0.22	1225	1005		
	Hollow clay brick - Ziegel - 8 cm	0.08	0.258	620	1000		
	Plaster - MapeWall	0.02	0.9	1250	1000		





• The user can define the roof stratigraphy separately for the reference roof (i.e., the original roof before the renovation, or a first roof option) in the "Select Reference Roof" section (A), and for the new roof (i.e., the roof after renovation, or a second roof option) "Select New Roof" section (B).

	A	Select Reference Roof ()			В	Select New Roof ①		
		Roof_02		X -			Roof_06		× *
Material Name	Thickness [m]	Thermal Conductivity [W/mK]	Density [kg/m3]	Specific Heat [J/kgK]	Material Name	Thickness [m]	Thermal Conductivity [W/mK]	Density [kg/m3]	Specific Heat [J/kgK]
Aluminium roof covering	0.0007	220	3319	896	Portoguese Clay tiles_1	0.011	1	2000	800
Elastoplastomeric polymer b	0.004	0.2	1150	1500	Roofing and waterproofing sy	0.0015	0.23	1000	1000
Extruded Polystyrene Insulat	0.06	0.031	41.3	1000	EPS insulation panel - Greyd	0.08	0.03	35	1450
Block for brick-cement floor	0.18	0.386	480	1000	Block for brick-cement floor	0.18	0.386	480	1000
					Plaster - MapeWall	0.02	0.9	1250	1000

In particular, the user can specify whether the roof is a HEROTILE-Based Roof (HBR) by checking the appropriate box (1) and select a predefined roof type in drop-down menu (2). Once a roof is selected, its stratigraphy will be shown in table (3).

Alternatively, a custom stratigraphy can be created on the *Edit > Roofs* page (see guide Section *3.4.2 Edit > Roofs*).

2	Select Reference Roof (i) Select if roof is HBR							
Roof_02 × 👻								
3	Material Name	Thickness [m]	Thermal Conductivity	Density [kg/m3]	Specific Heat [J/kgK]			
A	luminium roof cover	0.0007	220	3319	896			
El	lastoplastomeric pol	0.004	0.2	1150	1500			
E	xtruded Polystyrene	0.06	0.031	41.3	1000			
в	lock for brick-cemei	0.18	0.386	480	1000			







Once the Input Data phase is complete, click the **Run** button to perform the energy simulation of the attic floor for both the *reference* and *new roof configurations*.



For both the solutions the user is now able to read:

- the cooling energy demand
- the heating energy demand
- the maximum roof surface temperature

	Energy Simulation	
	Reset	
Cooling Energy Demand: 23 kWh/m2 year	I	Cooling Energy Demand: 14 kWh/m2 year
Heating Energy Demand: 29 kWh/m2 year		Heating Energy Demand: 30 kWh/m2 year
Maximum Roof Surface Temperature: 85.29 °C max temp		Maximum Roof Surface Temperature: 55.55 °C max temp



3.2.2 Life Cycle Costing

From the **Home** (1), in the **LIFE CYCLE COSTING** page (2), the user selects the Input Data in order to perform the LCC based on cooling energy benefits of the new roof and o the macroeconomic input data (Nominal Interest Rate, Inflation rate, Nominal Wage GDP, Electricity Price growth) that can be modified in Edit/Economic data (see guide Section **3.4.4** *Edit > Economic data*).

In particular, the user can choose:

- Calculation Period [years] (3)
- Service Life of the new roof [years] (4) for the calculation of the replacement cost and of the residual value of the roof at the end of the calculation period
- Investment Cost [€/m²] (5), i.e., extra-cost compared to building the 'reference roof'. Cost savings can be considered by using negative values.
- Periodic Maintenance Cost [€/m²] (6), i.e., extra-cost compared to maintaining the 'reference roof'. Cost savings can be considered by using negative values
- Periodic Maintenance Timing [years] (7)
- Cooling Energy Efficiency [-] (8), i.e., Coefficient of Performance for the electric cooling system
- Energy Tariff [€/kWh] (9)

1./	NIN SUPERHERO		* (
Home Exp	port - Edit - Help	2	
		LIFE CYCLE COSTING	
		Life Cycle Costing	
_		Based on cooling energy benefits of the new roof	
	Calculation Period (years)	Input Data () 5 Investment Cost [6/m2] () 40.42 6 Periodic Maintenance Cost [6/m2] () 7 Periodic Maintenance Timing (pears) 3	 Energy Efficiency [-] O Energy Tariff (C/Wh) 0,286

The calculation may take a few seconds. Once finished, results will appear. They are:

- Global costs at the end of calculation period [€/m²] (A), considering the initial investment extra-cost, the energy savings compared to the reference roof, the maintenance extra-cost and the residual value of the new roof at the end of the calculation period.
- Cumulative Discounted Cash Flows [€/m²] and Payback Period [years] (B). The Payback period, if any, is obtained in the year when cash flows reach a negative value.
- Present Values (C) for each year of the calculation period, including:
 - Cooling energy cost of the reference roof [€/m²]
 - Cooling energy cost of the new roof $[\pounds/m^2]$
 - Cooling energy savings [€/m²]
 - Maintenance cost [€/m²]
 - Replacement cost [€/m²]





		Present Values	
Years	Cooling energy cost of the reference roof [C/m2]	Cooling energy cost of the new roof [C/m2]	Cooling energy Savings [C/m2]
1	6.641	4.042	2.599
2	6.705	4.081	2.624
3	6.77	4.121	2.649
4	6.835	4.16	2.674
5	6.9	4.2	2.7
6	6.967	4.241	2.726
7	7.034	4.281	2.752
8	7.101	4.323	2.779
9	7.17	4.364	2.806
10	7.239	4.406	2.832
Years	Maintenance Cost [€/m2]		Replacement Cost [C/m2]
1	0		0
2	0		0
3	0		0
4	0.783		0
5	0		0
6	0		0
7	0.717		0
8	0		0
9	0		0
10	0.657		0





3.2.3 Life Cycle Assessment

Environmental impact assessment of the new roof based on product and operational cooling energy use stages can be performed from the Home (1), in the LIFE CYCLE ASSESSMENT page (2).

1 _#	IFE SUPERHERO		* 💽 C	
Home Export Edit Help			- 2	k
ROOF ENERGY PE		LIFE CYCLE COSTING	LIFE CYCLE ASSESSMENT	
		Life Cycle Assessment		
	Environmental imp	pact assessment of the new roof based on product and operational cooling energy use	stages	

The user has the option to include, within the already defined roof stratigraphy (see guide Section **3.2.1** *Roof Energy Performance*), additional materials that are part of the roof but do not contribute to the energy calculation (e.g., battens, special components, etc.).

The user should provide the following information:

- baseName EPD Material for which an EPD or Impact Table already exists in the tool database (1) Note:
 - Check if the material exists (see guide Section 3.4.1 Edit > Materials)
 - Upload existing EPD in. xIml format (see guide Section **3.4.5** Edit > Database of EPD)
 - Or create a new Impact Table (see guide Section 3.4.6 Edit > Create a new Impact Table)
- Functional Unit as reported in the EPD or in the Impact Table (2)
- Conversion Factor to relate the functional unit to 1 m² of roof surface (3)

The user can add as many materials as needed by inserting new rows (4) and then confirming the selection (5).

	Additional Materials to be included in the LCA $\textcircled{0}$	4.4
baseName EPD	2 Functional Unit	Conversion to m2
L	. (,	
	Add Row Confirm	7
	4 5	
	baseName EPD ()	





The user can check the name of the new roof selected (1) (see guide section **3.2.1** Roof Energy Performance). The calculation may take a few seconds. Once finished, results will appear (2).

	1 New Root: Rool_D6 💿 🔶		
	Global Warming Potential (GWP) [kg CO2 eq]		
	index	A1-A3	`` `
- ,	global warming potential (gwp)	65.806	N.
- i	global warming potential (gwp-ghg)	3.33	1
1	global warming potential - biogenic (gwp-biogenic)	-0.021	1
1	global warming potential - fossil fuels (gwp-fossil)	3.49	
1	global warming potential - land use and land use change (gwp-luluc)	0.002	
1	global warming potential - total (gwp-total)	3.47	
11	index B6		
	global warming potential (gwp) 5.756716		i i
1	global warming potential - biogenic (gwp-biogenic) 0.464366		1
11	global warming potential - fossil (gwp-fossil) 5291188		1
11	global warming potential - land use and land use change (gwp-luluc) 0.001176		
	Acidification Potential of soil and water (AP) [mol H+ eq]		;
1	index	A1-A3	
4.	acidifcation potential, accumulated exceedance (ap)	0.011	
- i -	acidification potential (ap)	0.068	1
÷1.	acidification potential of soil and water (ap)	0.032	I
11	index Bé		
1	acidification potential (ap) 0.022778		
١	Europhication Potential (EP) marine (kg N eq) freshwater (kg P eq) terrestrial (mol N eq)		;
1	index	A1-A3	1
	europhication potential - freshwater (ep-freshwater)	0	1
	europhication potential - marine (ep-marine)	0.002	





3.3 Export

Once the calculation is performed, energy model results can be saved as .dxf file or .IDF files with the Export menu. It also possible to download an Error log file .err



3.4 Edit

In the Edit page user can check or modify the database of:

- MATERIALS
- ROOFS
- WALLS
- EPD and Impact Tables
- Energy use conversion factor

	PESTIVITED 1	* <mark>()</mark> (
Materials		
Roofs		
Walls		
Economic data		
Database of EPDs and Impact Table		
Create a New Impact Table		
Energy Use Conversion Factor		
	-	

3.4.1 Edit > Materials

To create a new material, the user must go to Edit (1) and select Materials (2) The user should provide the following information:

- Material Name (3)
- Thickness [m] (4)
- Thermal Conductivity [W/mK] (5)
- Density [kg/m3] (6)
- Specific Heat [J/kgK] (7)

For materials used in the building envelope (walls and roofs), optical properties must be specified to enable energy calculations:

- Thermal Emissivity (8)
- Solar Absorptance (9)
- Visible Absorptance (10)





Note:

The user must then assign an **EPD or Impact Table** from those available in the software (**11**); or create a new one (see guide Section **3.4.6 Edit > Create a new Impact Table**); or upload an EPD in. xImI format (see guide Section **3.4.5 Edit > Database of EPD and Impact Tables**).

Additionally, the user must provide: **Functional Unit** as reported in the EPD or in the Impact Table (**12**), and a **Conversion Factor** to relate the functional unit to 1 m² of roof surface (**13**). Once all required information is entered, click Add Materials (**14**) to confirm.



The user can review the available materials in the tables below and modify existing properties by entering new values. To save the changes, click the appropriate confirmation buttons.

	Edit Materials						
	Material Name	Thickness [m]	Thermal Conductivity [W/mK]	Density [kg/m3]	Specific Heat [J/kgK]		
×	Glass Wool Insulation	0.09	0.0375	19	1000		
×	Aluminium roof covering	0.0007	220	3319	896		
× 6	Elastoplastomeric polymer bitumen membr	0.004	0.2	1150	1500		
	Confirm materials Material's Optical Properties ①						
	Material Name	Thermal Emissivi	ty	Solar Absorptance	Visible Absorptance		
×	Glass Wool Insulation	0.9		0.7	0.7		
×	Aluminium roof covering	0.4		0.8	0.8		
×	Elastoplastomeric polymer bitumen membrane	0.9		0.6	0.6		
	Confirm materials						

The user can check the available Environmental Impact Data in the table below:

Environmental Impacts Data				
Material Name	Functional Unit	baseName EPD	Conversion to m2	
Portoguese Clay tiles_1	t	Tegola portoghese tipo UNICOPPO e TE.SI	0.049225	
Portoguese Clay tiles_2	t	Tegola portoghese tipo UNICOPPO e TE.SI	0.049225	
Glass Wool Insulation	m2	S-P-06611 Isover Standard 90 mm	1	
Aluminium roof covering	m2	S-P-06249 Coperture metalliche & rivestimenti di facci	1	
Expanded Polystyrene Insulation (EPS)_1	m3	ECO-DUR ZETA	0.1	
Elastoplastomeric polymer bitumen membrane	m2	S-P-06507 Polyflex Light Evolution P	1	
Marsilleise Clay tiles_1	t	Tegola marsigliese rossa in laterizio	0.042	
Expanded Polystyrene Insulation (EPS)_2	m3	Eco Espanso 100	0.1	
Roofing and waterproofing synthetic membrane	m2	S-P-00906 Mapeplan T TPO/FPO Waterproofing Membr	1	
Steel Profiles	m2	S-P-06895 Building Steel Profiles	1	
Roofing and waterproofing PVC-P membrane	m2	S-P-00691 DANOPOL PVC Waterproofing sheet	1	
Extruded Polystyrene Insulation (XPS)_1	m2	S-P-07847 Sopra XPS	1	





3.4.2 Edit > Roofs

To create a new Roof Stratigraphy, the user must go to Edit (1) and select Roofs (2).

Next, the user should enter a name for the new roof in the designated field (3) and select the first material (4).

Additional materials can be added as needed by inserting new rows (5) and then confirming the selection (6). The material properties will be automatically populated based on the information provided in the **Edit** > **Materials** section.

	1	Ife SUPERHERO		*	c
Home Ex	mort * [_Edit *] Help				
	Materials				
	Walls				
	Economic data				
	Database of EPDs and Impact Tabl	es			
	Create a New Impact Table				
	Energy Use Conversion Factor				
10			Roof Stratigraphy		
			Name of the Roof Stratigraphy		
			3 Type the name here		
4	Material Name	Thickness [m]	Thermal Conductivity [W/mK]	Density [kg/m3]	Specific Heat [J/kgK]
×		- 🖊			
×					
			Add Row Confirm 5 6		

The user can view existing roofs stratigraphy in the table below by selecting a roof from the list:

Visualize Roofs				
		Roof_06		× 👻
Material Name	Thickness [m]	Thermal Conductivity [W/mK]	Density [kg/m3]	Specific Heat [J/kgK]
Portoguese Clay tiles_1	0.011	1	2000	800
Roofing and waterproofing synthetic	0.0015	0.23	1000	1000
EPS insulation panel - Greydur Top 3	0.08	0.03	35	1450
Block for brick-cement floor 18x25x4	0.18	0.386	480	1000
Plaster - MapeWall	0.02	0.9	1250	1000
		Reset		





3.4.3 Edit > Walls

To create a new Wall Stratigraphy, the user must go to Edit (1) and select Walls (2).

Next, the user should enter a name for the new wall in the designated field (3) and select the first material (4).

Additional materials can be added as needed by inserting new rows (5) and then confirming the selection (6). The material properties will be automatically populated based on the information provided in the **Edit** > **Materials** section.



The user can view existing walls stratigraphy in the table below by selecting a roof from the list:

Walls				
		Wall_03		× +
Material Name	Thickness [m]	Thermal Conductivity [W/mK]	Density [kg/m3]	Specific Heat [J/kgK]
Plaster – MapeWall	0.02	0.9	1250	1000
Hollow clay brick - Ziegel - 12 cm	0.12	0.258	620	1000
Air gap - 4 cm	0.04	0.22	1225	1005
Hollow clay brick - Ziegel - 8 cm	0.08	0.258	620	1000
Plaster - MapeWall	0.02	0.9	1250	1000
		Reset		





3.4.4 Edit > Economic data

By going to Edit (1) and selecting Economic data (2), the user can modify all macroeconomic constants and/or year-by-year variable values. Once the edits are complete, confirmation is required by clicking the designated button.

1				* C
Home Excort Edit" Materials 21 Economic Database Create at Energy Un	Help deta of EPDs and Impact Tables. New Impact Table de Colversion Factor			
		Macroeconon	nic Input Data	
		Costan	t values	
Nominal	Interest Rate	Inflation Rate	Nominal Wage (GDP)	Electricity Price Growth
(0,04	0,02 Edit	0,01 data	0,05
Macroeconomics Input Data				
Variable values over the years ①				
Years	Nominal Interest Rate	Inflation	Nominal Wage GDP	Electricity Price Growth
1	0.04	0.02	0.01	0.05
2	0.04	0.02	0.01	0.05
3	0.04	0.02	0.01	0.05
4	0.04	0.02	0.01	0.05
5	0.04	0.02	0.01	0.05
		Confirm da	ita Reset	





3.4.5 Edit > Database of EPD and Impact Tables

To create a new EPD the user must go to **Edit (1)** and select **Database of EPD and Impact Tables (2)**. The user can then drag and drop a new EPD file in .xml format into the designated area and click **Update** to upload it.

6		Ife SUPERHERO	*C	
Home Export * [
	Materials			
	Roofs			
	Walls			
9	Economic data			
-	Database of EPDs and impact Tabl	les .		
	Create a New Impact Table			
	Create a New Impact Table			
	Energy Use Conversion Pactor			
		Add EPD		
,				
		Designed Designed (see at		
		Drag and Drop EPD in Xml format		Update
ι				

On the same page, it is possible to view the list of the existing uploaded EPDs.

Uploaded EPDs List		
baseName EPD	UUD	
database-Greydur Top B_100% recycled-1	epd-database-pdf-1	
database-Greydur Top B-0	epd-database-pdf-0	
database-Sopro Fliesenfest extra FF 450-2	epd-database-pdf-2	
database-Mapei Polyglass ANTIRADICE LIGHT P-7	epd-database-pdf-7	
S-P-00691 DANOPOL PVC Waterproofing sheet	6b7911c8-7933-42ea-9309-41f907f28939	
Tegola portoghese tipo UNICOPPO e TE.SI	07ab1c07-ee4e-44c5-9c83-959fb0446bb4	
database-MR_Rothoblaas Transpir Evo Seal 200-3	epd-database-pdf-3	

On the same page, it is also possible to view the Life Cycle Impact Assessment (LCIA) results of a specific material across its entire life cycle, quantified by specific environmental impact categories, and export the data.

	LCIA Results 🥜 Select		
		database-Greydur Top B-0	
Export		Global Warming Potential (GWP) [kg CO2 eq]	
	database-Greydur Top B-0		global warming potential (gwp)
	A1-A3		127
	C2		0.15
	C3		81.2
	D		-33.7
Export		Acidification potential of soil and water (AP) [mol H+ eq]	
	database-Greydur Top B-0		acidification potential (ap)
	A1-A3		0.135
	C2		0
	C3		0.007
	D		-0.045
Export		Europhication Potential (EP) marine [kg N eq] freshwater [kg P eq] terrestrial [mol N eq]	
	database-Greydur Top B-0		eutrophication potential (ep)
	A1-A3		0.451
	C2		0.001
	C3		0.034
	n		-0.137



3.4.6 Edit > Create a new Impact Table

In **Edit** (1) > **Create a new Impact Table** (2). The user can generate a new table reporting environmental impacts in the EPD format. To do so, edit the values directly in the table rows and then click the Update button to save the changes.







3.4.7 Edit > Energy Use Conversion Factors

In **Edit (1)** > **Energy Use Conversion Factors (2)**, the user can modify values directly in the table rows and then click the *Confirm Data* button to save the changes. These values are calculated based on: 1 kWh Electricity, low voltage – UNI EN 15804 + A2 (adapted), Version 1.00 / EF 3.1 normalization and weighting set, October 2023.

	*
Rome Exact Edv Help Materials Roofs Walls Economic data Database of EPDs and impact Tables Create a New Impact Tables Create a New Impact Table	and a factor o
11A - 10	117
index	ITA - Italy
acidification potential (ap)	0.001627
global warming potential (gwp)	0.411194
global warming potential - biogenic (gwp-biogenic)	0.033169
global warming potential - fossil (gwp-fossil)	0.377942
global warming potential - land use and land use change (gwp-luluc)	0.000084
eutrophication potential - marine (ep-marine)	0.000249
eutrophication potential - freshwater (ep-freshwater)	0.000082
eutrophication potential - terrestrial (ep-terrestrial)	0.00285
ozone depletion (odp)	0
photochemical ozone formation (pocp)	0.001189
abiotic depletion potential - fossils resources(adpf)	5.897616
abiotic depletion potential - non fossil resources (adpe)	0.000004
Confirm da	la Reset

